

SAE

Scientific Audio Electronics, Inc.

AT-2000 Series

The AT-2000 "Pure Balance"® series feature ALL the same design elements of the AT-3000 except that the power output is 200 W RMS/channel into 8 Ohms. Configurations are available from 2 to 7 channels. Additional modules are available.

See below for additional features common to all S.A.E. models.

Remote Trigger:	Activated from 3.3VDC to 24 VDC via a heavy-duty relay
Protection Circuits:	Optically –coupled with full automatic reset.
Toroid Transformers:	40% more efficient than EI type. Separate bi-filar windings for each channel guaranty lower noise and crosstalk.
Circuit Boards:	Double-sided, FR-4 glass-epoxy, computer-grade boards are assembled in-house.
Soft Start Circuitry:	Ultra soft turn on reduces in-rush current to a minimum. Multiple units can be turned on without tripping circuit breakers eliminating the need for sequencing.
Power Transistors:	High-current, bi-polar output transistors with active bias circuits result in effortless operation.
Power Cord:	Detachable, 3-wire cord.
7-Year Warranty	Parts and labor against defects in parts or workmanship.
Dimensions:	17" w X 7" h X 17" d (<i>chassis</i>) weight - 50 to 95lbs (<i>model dependent</i>)



LEONARDO MANI AUDIO

C.P. 4358 50135 FIRENZE Cell 333 2233000 Fax 055 570483

www.audiomani.it